

What is claimed is:

1 1. A network architecture for Wireless Intranet Office (WIO) applications,
2 comprising:
3 a wireless local area network (WLAN) comprising a Wireless Mobile Center (WMC)
4 arranged to serve as a WLAN access point;
5 a GSM network comprising a Mobile Station (MS) in a form of a dual-mode cellular
6 phone to access both WLAN and GSM radio technologies, a Base Station (BS) arranged to
7 convert a radio signal from the Mobile Station (MS) for communication, a Mobile Switching
8 Center (MSC) arranged to establish call connection; and
9 a Handover Module implemented in either the Mobile Station (MS) or the Wireless
10 Mobile Center (WMC) for providing seamless mobility between said GSM network and said
11 wireless LAN, when the Mobile Station (MS) roams between said GSM network and said
12 wireless LAN.

1 2. The network architecture as claimed in claim 1, wherein, during an IDLE mode
2 when the Mobile Station (MS) roams from said GSM network to said wireless LAN, the Mobile
3 Station (MS) selects a WLAN radio and attempts a location update via said wireless LAN, and a
4 new location of the Mobile Station (MS) is updated at the Mobile Switching Center (MSC).

1 3. The network architecture as claimed in claim 1, wherein, during an ACTIVE
2 handover mode when the Mobile Station (MS) initiates a handover from said GSM network to
3 said wireless LAN, the Mobile Station (MS) measures GSM neighbor cells and reports a WLAN
4 cell as an ordinary GSM cell, enables transmission of a handover request to the Mobile Switching
5 Center (MSC) of said GSM network, until the Mobile Station (MS) is handed over to said
6 wireless LAN.

1 4. The network architecture as claimed in claim 1, wherein, during an IDLE mode
2 when the Mobile Station (MS) roams from said wireless LAN to said GSM network, the Wireless
3 Mobile Center (WMC) informs GSM neighbor cells, and the Mobile Station (MS) selects a GSM
4 radio and attempts a location update via said GSM network, and a new location of the Mobile
5 Station (MS) is updated at the Mobile Switching Center (MSC).

1 5. The network architecture as claimed in claim 1, wherein, during an ACTIVE
2 handover mode when the Mobile Station (MS) initiates a handover from said wireless LAN to
3 said GSM network, the Mobile Station (MS) measures GSM neighbor cells, enables transmission
4 of a handover request to the Mobile Switching Center (MSC), via the Wireless Mobile Center

1 (WMC) of said wireless LAN, until the Mobile Station (MS) is handed over to said GSM
2 network.

1 6. The network architecture as claimed in claim 1, wherein, during an IDLE mode
2 when the Mobile Station (MS) roams from said GSM network to said wireless LAN, the Mobile
3 Station (MS) first camps in said GSM network, measures GSM neighbor cells for a WLAN cell,
4 and when a WLAN transmission level is acceptable, attempts a location update, via said wireless
5 LAN, and when the location update is accepted, camps in said wireless LAN and remains ready to
6 make a call.

1 7. The network architecture as claimed in claim 1, wherein, during an ACTIVE
2 handover mode when the Mobile Station (MS) initiates a handover from said GSM network to
3 said wireless LAN:

4 said Mobile Station (MS) measures GSM neighbor cells, reports measurement results,
5 determines if a WLAN transmission level exceeds a limit and, if said WLAN transmission level
6 exceeds a limit, list a WLAN cell first in said measurement results;

7 said Base Station (BS) receives said measurement results, and indicates a handover to a
8 WLAN cell; and

9 said Mobile Station (MS) is handed over to said wireless LAN.

1 8. The network architecture as claimed in claim 1, wherein, during an IDLE mode
2 when the Mobile Station (MS) roams from said wireless LAN to said GSM network:
3 said Wireless Mobile Center (WMC) informs GSM neighbor cells; and
4 said Mobile Station (MS) first camps in said wireless LAN, measures a WLAN cell and
5 informed GSM neighbor cells, determines if a WLAN transmission level drops below a limit and,
6 if the WLAN transmission level drops below the limit, camps in said GSM network based on
7 predetermined variables, makes a location update via said GSM network.

1 9. The network architecture as claimed in claim 1, wherein, during an ACTIVE
2 handover mode when the Mobile Station (MS) initiates a handover from said wireless LAN to
3 said GSM network:
4 said Mobile Station (MS) measures a WLAN cell and informed GSM neighbor cells, and
5 sends an indication if a WLAN transmission level drops below limit;
6 said Wireless Mobile Center (WMC) calculates the best GSM target cell, and starts a
7 handover;
8 said Base Station (BS) sends GSM neighbor cells to said Mobile Station (MS) in response
9 to a handover attempt; and
10 said Mobile Station (MS) is handed over to said GSM network.

1 10. A network architecture, comprising:
2 a local radio network comprising a Wireless Mobile Center (WMC) arranged to serve as a
3 WLAN access point;
4 a GSM network comprising a Mobile Station (MS) in a form of a dual-mode cellular
5 phone operable in both said local radio network and said GSM network, a Base Station (BS)
6 arranged to convert a radio signal from the Mobile Station (MS) for communication, a Mobile
7 Switching Center (MSC) arranged to establish call connection; and
8 a Handover Module implemented in either the Mobile Station (MS) or the Wireless
9 Mobile Center (WMC) for providing seamless mobility between said local radio network and said
10 GSM network, when the Mobile Station (MS) roams between said local radio network and said
11 GSM network.

1 11. The network architecture as claimed in claim 10, wherein said local radio network
2 corresponds to a wireless local area network (LAN) that is located in hotspot areas or an area
3 where a higher bit rate or high quality of service (QoS) is desired, and uses a radio technology
4 that is different from said GSM network.

1 12. The network architecture as claimed in claim 11, wherein, during an IDLE mode
2 when the Mobile Station (MS) roams from said GSM network to said wireless LAN, the Mobile
3 Station (MS) selects a WLAN radio and attempts a location update via said wireless LAN, and a
4 new location of the Mobile Station (MS) is updated at the Mobile Switching Center (MSC).

1 13. The network architecture as claimed in claim 11, wherein, during an IDLE mode
2 when the Mobile Station (MS) roams from said GSM network to said wireless LAN, the Mobile
3 Station (MS) selects a WLAN radio and attempts a location update via said wireless LAN, and a
4 new location of the Mobile Station (MS) is updated at the Mobile Switching Center (MSC).

1 14. The network architecture as claimed in claim 11, wherein, during an ACTIVE
2 handover mode when the Mobile Station (MS) initiates a handover from said GSM network to
3 said wireless LAN, the Mobile Station (MS) measures GSM neighbor cells and reports a WLAN
4 cell as an ordinary GSM cell, enables transmission of a handover request to the Mobile Switching
5 Center (MSC) of said GSM network, until the Mobile Station (MS) is handed over to said
6 wireless LAN.

1 15. The network architecture as claimed in claim 11, wherein, during an IDLE mode
2 when the Mobile Station (MS) roams from said wireless LAN to said GSM network, the Wireless

3 Mobile Center (WMC) informs GSM neighbor cells, and the Mobile Station (MS) selects a GSM
4 radio and attempts a location update via said GSM network, and a new location of the Mobile
5 Station (MS) is updated at the Mobile Switching Center (MSC).

1 16. The network architecture as claimed in claim 11, wherein, during an ACTIVE
2 handover mode when the Mobile Station (MS) initiates a handover from said wireless LAN to
3 said GSM network, the Mobile Station (MS) measures GSM neighbor cells, sends a handover
4 request to the Mobile Switching Center (MSC), via the Base Station (BS) of said GSM network,
5 until the Mobile Station (MS) is handed over to said GSM network.

1 17. A method for providing seamless mobility for a Mobile Station (MS) between a
2 GSM network having a Base Station (BS) and a Mobile Switching Center (MSC), and a wireless
3 local area network (LAN) having a Wireless Mobile Center (WMC) arranged to serve as an
4 access point and linked to said Mobile Switching Center (MSC) via said LAN, comprising:

5 during an IDLE mode in said GSM network, selecting a WLAN radio and requesting a
6 location update at said Mobile Switching Center (MSC), via said wireless LAN;

7 alternatively in said wireless LAN, selecting a GSM radio and requesting a location update
8 at said Mobile Switching Center (MSC), via said GSM network;

9 during an ACTIVE handover mode, measuring GSM neighbor cells to report a WLAN
10 cell as an ordinary GSM cell, sending a handover request to said Mobile Switching Center (MSC)
11 of said GSM network, via said Base Station (BS) of said GSM network, until a handover is
12 completed in said wireless LAN; and

13 alternatively, measuring GSM neighbor cells and sending a handover request to said
14 Mobile Switching Center (MSC), via said Wireless Mobile Center (WMC) of said wireless LAN,
15 until said handover is completed in said GSM network.

1 18. The method as claimed in claim 17, wherein said Mobile Station (MS) is a dual-
2 mode cellular phone operable in both said wireless LAN and said GSM network.

1 19. The method as claimed in claim 17, wherein said wireless LAN is located in
2 hotspot areas or an area where a higher bit rate or high quality of service (QoS) is desired, and
3 uses a radio technology that is different from said GSM network.

1 20. The method as claimed in claim 17, wherein said Mobile Station (MS) and said
2 Wireless Mobile Center (WMC) are either implemented with a Handover Module for controlling
3 said Mobile Station (MS) to handover seamlessly between said wireless LAN and said GSM

5 network.

add a^9

1991
 1992
 1993
 1994
 1995
 1996
 1997
 1998
 1999
 2000
 2001
 2002
 2003
 2004
 2005
 2006
 2007
 2008
 2009
 2010
 2011
 2012
 2013
 2014
 2015
 2016
 2017
 2018
 2019
 2020
 2021
 2022
 2023
 2024
 2025
 2026
 2027
 2028
 2029
 2030
 2031
 2032
 2033
 2034
 2035
 2036
 2037
 2038
 2039
 2040
 2041
 2042
 2043
 2044
 2045
 2046
 2047
 2048
 2049
 2050
 2051
 2052
 2053
 2054
 2055
 2056
 2057
 2058
 2059
 2060
 2061
 2062
 2063
 2064
 2065
 2066
 2067
 2068
 2069
 2070
 2071
 2072
 2073
 2074
 2075
 2076
 2077
 2078
 2079
 2080
 2081
 2082
 2083
 2084
 2085
 2086
 2087
 2088
 2089
 2090
 2091
 2092
 2093
 2094
 2095
 2096
 2097
 2098
 2099
 2100
 2101
 2102
 2103
 2104
 2105
 2106
 2107
 2108
 2109
 2110
 2111
 2112
 2113
 2114
 2115
 2116
 2117
 2118
 2119
 2120
 2121
 2122
 2123
 2124
 2125
 2126
 2127
 2128
 2129
 2130
 2131
 2132
 2133
 2134
 2135
 2136
 2137
 2138
 2139
 2140
 2141
 2142
 2143
 2144
 2145
 2146
 2147
 2148
 2149
 2150
 2151
 2152
 2153
 2154
 2155
 2156
 2157
 2158
 2159
 2160
 2161
 2162
 2163
 2164
 2165
 2166
 2167
 2168
 2169
 2170
 2171
 2172
 2173
 2174
 2175
 2176
 2177
 2178
 2179
 2180
 2181
 2182
 2183
 2184
 2185
 2186
 2187
 2188
 2189
 2190
 2191
 2192
 2193
 2194
 2195
 2196
 2197
 2198
 2199
 2200
 2201
 2202
 2203
 2204
 2205
 2206
 2207
 2208
 2209
 2210
 2211
 2212
 2213
 2214
 2215
 2216
 2217
 2218
 2219
 2220
 2221
 2222
 2223
 2224
 2225
 2226
 2227
 2228
 2229
 2230
 2231
 2232
 2233
 2234
 2235
 2236
 2237
 2238
 2239
 2240
 2241
 2242
 2243
 2244
 2245
 2246
 2247
 2248
 2249
 2250
 2251
 2252
 2253
 2254
 2255
 2256
 2257
 2258
 2259
 2260
 2261
 2262
 2263
 2264
 2265
 2266
 2267
 2268
 2269
 2270
 2271
 2272
 2273
 2274
 2275
 2276
 2277
 2278
 2279
 2280
 2281
 2282
 2283
 2284
 2285
 2286
 2287
 2288
 2289
 2290
 2291
 2292
 2293
 2294
 2295
 2296
 2297
 2298
 2299
 2300
 2301
 2302
 2303
 2304
 2305
 2306
 2307
 2308
 2309
 2310
 2311
 2312
 2313
 2314
 2315
 2316
 2317
 2318
 2319
 2320
 2321
 2322
 2323
 2324
 2325
 2326
 2327
 2328
 2329
 2330
 2331
 2332
 2333
 2334
 2335
 2336
 2337
 2338
 2339
 2340
 2341
 2342
 2343
 2344
 2345
 2346
 2347
 2348
 2349
 2350
 2351
 2352
 2353
 2354
 2355
 2356
 2357
 2358
 2359
 2360
 2361
 2362
 2363
 2364
 2365
 2366
 2367
 2368
 2369
 2370
 2371
 2372
 2373
 2374
 2375
 2376
 2377
 2378
 2379
 2380
 2381
 2382
 2383
 2384
 2385
 2386
 2387
 2388
 2389
 2390
 2391
 2392
 2393
 2394
 2395
 2396
 2397
 2398
 2399
 2400
 2401
 2402
 2403
 2404
 2405
 2406
 2407
 2408
 2409
 2410
 2411
 2412
 2413
 2414
 2415
 2416
 2417
 2418
 2419
 2420
 2421
 2422
 2423
 2424
 2425
 2426
 2427
 2428
 2429
 2430
 2431
 2432
 2433
 2434
 2435
 2436
 2437
 2438
 2439
 2440
 2441
 2442
 2443
 2444
 2445